



GENERAL NOTES:

ALL DIMENSIONS SHOWN ARE IN mm UNLESS OTHERWISE NOTED.

STAPLES AT JOINTS AND ENDS:

THE NETTING SHALL BE SECURED WITH STAPLES PLACED ON 300 mm CENTERS AT BOTH ENDS OF THE NETTING AND AT ALL TRANSVERSE AND LONGITUDINAL JOINTS.

TRANSVERSE STAPLE LINES:

A LINE OF TRANSVERSE STAPLES WILL BE PLACED AT 1500 mm LONGITUDINAL INCREMENTS; A STAPLE WILL BE PLACED AT ALL SLOPE CHANGES IN THE DITCH CROSS SECTION AND AT THE OUTER EDGES OF THE NETTING. INTERMEDIATE STAPLES BETWEEN THE OUTER EDGES AND BETWEEN THE SLOPE CHANGES SHALL BE PLACED AT MAXIMUM 600 mm SPACING, STAGGERED TO PREVENT STRAIGHT LONGITUDINAL LINES OF STAPLES.

MISSOURI HIGHWAY AND TRANSPORTATION
COMMISSION

STAPLE PLACEMENT FOR PLASTIC NETTING

DATE: _____

EFFECTIVE: 02-01-1995

M806.02A

1
1